

CERTUSS

Steam Generators



CVE
Package plant unit

Ready-to-use water supply with CERTUSS package plant unit CVE

- all supply and water treatment components for CERTUSS steam generators as complete unit
- less space required due to compact design
- corrosion protection by galvanized base frame
- complete with electrical sub-distribution
- easy maintenance and access
- low-cost serial manufacture with optimally-coordinated components
- use of approved, high quality materials
- fast, economical installation, ready for operation in just a few hours
- safe due to factory pre-installation of water, steam, electrical and power connections
- simple on-site installation, no special knowledge required

Technical data

Type	For steam generators with steam output kg/h	Dimensions (~ mm)			Connections					Electrical connection	Connected electrical load * kW
		Height A	Width B	Depth C	Raw water DN	Waste water DN	Rinsing water (softening) DN	Ventilation (feed water tank) DN	Condensat DN		
Junior	80 - 120	1950	1350	890	1"	2"	1/2"	2"	1 1/4"	3 x 400 V / 50 Hz	2,0
	150 - 200										2,2
	250 - 400										2,3
	500 - 600										3,7
Universal	700 - 850	2300	1700	1250	1"	2"	1/2"	DN 100	1 1/2"		x,x
	1000 - 1300										x,x
	1500 - 1800										x,x
Universal	2 x 80 - 120	1950	1350	890	1"	2"	1/2"	2"	1 1/4"		2,0
	2 x 150 - 200										2,2
	2 x 250 - 400										2,3
	2 x 500 - 600									3,7	

* incl. connected load of steam generators

Right reserved to make technical changes.

CERTUSS Dampfautomaten GmbH & Co. KG
Hafenstraße 65 · 47809 Krefeld
Telefon +49 (0)2151 578-0 · Telefax +49 (0)2151 578-102
Internet: www.certuss.com · e-mail: verkauf@certuss.com

CERTUSS
Steam Generators

24.044.02.0196.02